

Legend

Variable Speed Direct Drive Fiberglass Exhaust Fan

A new line of fans is here. The Legend is an extremely versatile exhaust fan, capable of producing 5,000 CFM – 14,000 CFM at 0.05" SP, making this fan an ideal addition to your ventilation system. Producers still need ventilation in the winter months to exhaust stale, gas ridden air out of their barn or building. Slow down the Legend so you still get rid of the stale air, all while not creating a cold draft for your animals. Then in the summer months, ramp up the speed to provide a cool breeze.

**5,000-14,000
CFM @
0.05" SP**



**NEW fan series.
More sizes coming soon!**



Shown with shutter removed
(Never permit power to fan with shutter removed)

Part #	Sz	Spd	@ 0.05" SP			@ 0.10" SP			Drive	Prop
			CFM	CFM/ Watt	FEI	CFM	CFM/ Watt	FEI		
Single Phase With Cone										
Aluminum Shutter										
VLA36S3C11A-PM	36"	1/V^	100% 14,004	16.1	1.79	13,154	14.6	1.83	PM-DD	3-SS
			90% 12,303	19.8	2.26	11,654	17.7	2.24		
			80% 10,690	24.2	2.81	10,003	21.4	2.75		
			70% 8,929	29.1	3.45	7,917	24.1	3.19		
			60% 7,097	33.8	4.12	5,623	25.1	3.48		
Poly Shutter										
VLP36S3C11A-PM	36"	1/V^	100% 13,733	15.8	1.77	13,085	14.3	1.79	PM-DD	3-SS
			90% 11,829	18.6	2.14	11,171	16.8	2.13		
			80% 10,248	23.3	2.14	9,352	19.9	2.13		
			70% 8,414	27.6	3.29	7,210	22.1	2.96		
			60% 6,483	31.3	3.86	4,720	20.9	2.97		
No Cone										
Aluminum Shutter										
VLA36S3N11A-PM	36"	1/V^	100% 12,855	14.1	1.61	12,294	13.0	1.63	PM-DD	3-SS
			90% 11,318	17.1	1.96	10,656	15.4	1.96		
			80% 9,733	21.4	2.50	8,753	18.3	2.39		
			70% 7,824	25.3	3.04	6,751	20.7	2.80		
			60% 6,065	29.3	3.66	4,782	21.6	3.07		
Poly Shutter										
VLP36S3N11A-PM	36"	1/V^	100% 12,535	13.4	1.53	11,872	12.3	1.55	PM-DD	3-SS
			90% 10,864	16.3	1.53	10,117	14.6	1.55		
			80% 9,161	19.9	2.35	8,362	17.6	2.30		
			70% 7,542	24.1	2.92	6,433	19.5	2.65		
			60% 5,707	27.3	3.45	4,392	19.5	2.82		

Rough Opening - 44½" W x 44½"H
Side-By-Side Recommended OC Dimension for Fan with Cone - Minimum 50"

Available in black.



^ Variable speed fans require separate variable speed control to adjust fan speed.

Bold red text is data based on testing performed by an accredited lab using ANSI/AMCA 210-07 standard.

When ordering black models add "-B" to the end of the part#.

Features

- Variable speed ready - NO VFD NEEDED!
- IP66-rated, direct drive motor
- Fiberglass housing does not rust or rot
- Stainless-steel motor frame, prop, & hardware - Corrosion-resistant
- Aluminum or poly shutter options
- Maintenance-free!
- No belts, pulleys, or tensioners
- Models with or without cone
- More sizes coming soon!
- Totally enclosed, maintenance-free, high-efficiency motors have completely sealed ball bearings, are CSA recognized, and are covered by a **2 Year Warranty**

⚠ WARNING: This product can expose you to chemicals including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov/product.