

# Twister Exhaust Fan

J&D Manufacturing's Twister Exhaust Fan remains unchanged after 25 years. Why change a fan that is this dependable? The Twister is manufactured with a heavy gauge housing and butterfly shutters that open easily on startup, and spring closed when not in use to create a tight weather seal.

## Features

- Aluminum prop with zinc plated hub is balanced for smooth vibration-free operation
- Hinged rear guard allows for easy cleaning and maintenance by simply removing two bolts and swinging out the fan assembly
- 18-gauge galvanized butterfly shutter has adjustable positive draft-free closure
- Fan comes fully assembled for easy installation
- Direct drive motor
- Heavy-duty 18-gauge galvanized housing
- Heavy-duty motor mount safety guard combination has an easy-to-clean coated finish
- Rear guard conforms to OSHA 1910.212(a)(5) safety requirements to mount at any height on motor side of fan (damper side should be mounted 7' above ground)
- Totally enclosed, maintenance-free, high-efficiency motors have completely sealed ball bearings, are UL and CUL recognized, and are covered by a **2 Year Warranty**
- Optional galvanized weather hood available to protect your fan from harsh weather and severe wind



| Part #              | Sz  | Spd | @0.10" SP    |             | Prop  | Rough Opening |
|---------------------|-----|-----|--------------|-------------|-------|---------------|
|                     |     |     | CFM          | Watt        |       |               |
| <b>Single Phase</b> |     |     |              |             |       |               |
| VFT141130           | 12" | 1   | 780          | 8.5         | 3-Alm | 13¾" x 13¾"   |
| VFT141131           | 16" | 1   | <b>2,050</b> | <b>7.7</b>  | 3-Alm | 18" x 18"     |
| VFT141132           | 20" | 1   | <b>2,630</b> | <b>9.7</b>  | 3-Alm | 22" x 22"     |
| VFT141133           | 24" | 1   | <b>4,470</b> | <b>11.7</b> | 3-Alm | 25¼" x 25¼"   |

\*


\* Experts choice

**Bold red text is data based on testing performed by an accredited lab using ANSI/AMCA Standard 210-07**

**OSHA requires this fan to be mounted with damper side of fan 7' above the floor**

## Optional Weather Hood

| Shutter Fan Size | Weather Hood |
|------------------|--------------|
| 12"              | VFT140855    |
| 16"              | VFT140856    |
| 20"              | VFT140857    |
| 24"              | VFT140858    |



Weather hood for exterior shutter side of fan

**⚠ WARNING:** This product can expose you to chemicals including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov/product](http://www.P65Warnings.ca.gov/product).