

# Poly Stormer

Keep air moving efficiently across your facility with J&D's Poly Stormer. Made with high CFM in mind, this economical fan will give you the efficiency you want and the airflow you deserve.

## Features

- Fan ships fully assembled
- Direct drive motor with no belts or bearings to maintain
- Totally enclosed, maintenance-free, high-efficiency standard motors have completely sealed ball bearings, are UL and CUL recognized, and are covered by a **2 Year Warranty**
- Gold Star Motors have a **3 Year Warranty**
- Polyethylene housing will not rust or corrode
- Stainless-steel fasteners, powder coated guards, and galvanized prop for long lasting corrosion-resistance
- Lightweight for easier installation
- Motors have built-in automatic thermal overload protection for the longest motor life possible
- Compatible with our misting/fogging product line



RECIRCULATION FANS

Part#	Size	Ph	Spd	Thrust CFM	Thrust CFM/Watt	Drive	Prop
<b>Single Phase</b>							
* VPS36A-GS	36"	1	1	<b>8,450</b>	<b>17.1</b>	Direct	3-Glv
<b>Three Phase</b>							
VPS36CF-GS	36"	3	1/Var^	<b>8,560</b>	<b>18.9</b>	Direct	3-Glv

Part#	Size	Ph	Spd	Thrust CFM	Thrust CFM/Watt	Drive	Prop
<b>Single Phase</b>							
VPS36A	36"	1	1	<b>8,210</b>	<b>16.3</b>	Direct	3-Glv
<b>Three Phase</b>							
* VPS36CF	36"	3	1	<b>8,460</b>	<b>18.7</b>	Direct	3-Glv

All Poly Stormer Fans include a hot dip galvanized mounting bracket



\* Experts choice

^ Variable speed fans require separate variable speed control to adjust fan speed

**Bold red text is data based on testing performed by an accredited lab using ANSI/AMCA Standard 230-12**  
**OSHA requires this fan to be mounted a minimum of 7' above the floor**

# High Output Deluxe Basket Fan

J&D Manufacturing's High Output Deluxe Basket Fan series combines high performance, economical pricing, and energy efficiency to give you one of the best valued fan series available on the market today.

## Features

- Fan ships completely assembled
- Direct drive - no belts or pulleys to maintain
- Heavy gauge, corrosion-resistant, black powder coated guards
- Single phase models include attached cord with 3-prong plug pre-wired for 115 Volts
- Guards meet OSHA 1910.212(a)(5) requirements allowing this fan to be installed at any height
- Totally enclosed, maintenance-free, high-efficiency motors feature sealed ball bearings and are covered by a **2 Year Warranty**
- Gold Star Motors have a **3 Year Warranty**
- Compatible with our misting/fogging product line



Part#	Size	Ph	Spd	Thrust CFM	Thrust CFM/Watt	Drive	Prop
<b>Single Phase</b>							
<b>With Cord</b> (pre-wired for 115V, electrician may rewire for 230V)							
VDB20-GS	20"	1	1	<b>3,920</b>	<b>8.9</b>	Direct	3-Alm
VDB24-GS	24"	1	1	<b>5,680</b>	<b>11.3</b>	Direct	3-Alm
VDB30-GS	30"	1	1	<b>6,380</b>	<b>12.4</b>	Direct	3-Alm
* VDB36-GS	36"	1	1	<b>9,160</b>	<b>17.4</b>	Direct	3-Glv
<b>Three Phase</b>							
<b>No Cord</b>							
VDB303-GS	30"	3	1	<b>6,380</b>	<b>13.7</b>	Direct	3-Alm
VDB363-GS	36"	3	1	<b>9,810</b>	<b>17.7</b>	Direct	3-Alm

Part#	Size	Ph	Spd	Thrust CFM	Thrust CFM/Watt	Drive	Prop
<b>Single Phase</b>							
<b>With Cord</b> (pre-wired for 115V, electrician may rewire for 230V)							
VDB20	20"	1	1	<b>3,340</b>	<b>9.1</b>	Direct	3-Alm
* VDB24	24"	1	1	<b>5,370</b>	<b>10.8</b>	Direct	3-Alm
VDB30	30"	1	1	<b>6,500</b>	<b>11.4</b>	Direct	3-Alm
VDB36	36"	1	1	<b>9,520</b>	<b>17.3</b>	Direct	3-Glv
<b>Three Phase</b>							
<b>No Cord</b>							
VDB303	30"	3	1	<b>6,730</b>	<b>13.0</b>	Direct	3-Alm
VDB363	36"	3	1	<b>9,500</b>	<b>19.4</b>	Direct	3-Glv

All High Output Deluxe Basket Fans include a hot dip galvanized mounting bracket



\* Experts choice

**Bold red text is data based on testing performed by an accredited lab using ANSI/AMCA Standard 230-12**

**⚠ WARNING:** This product can expose you to chemicals including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov/product](http://www.P65Warnings.ca.gov/product).